SAFETY DATA SHEET

1. Identification

Product identifier	Fresh Linen Metered Air Freshener	
Other means of identification		
Product code	YA038C	
Recommended use	AIR FRESHENER	
Recommended restrictions	None known.	
Manufacturer/Importer/Supplier/I	Distributor information	
Manufacturer		
Company name	Pro-Link Canada	
Address	Box 67082, 421 Richmond Road	
	Ottawa, Ontario K2A 4E4	
	Canada	
Telephone	General Assistance	613-722-0798
Website	www.prolinkcanada.com	
E-mail	Not available.	
Emergency phone number	Emergency - US	1-866-836-8855
	Emergency - Outside US	1-952-852-4646
Supplier	Not available.	

Supplier

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Serious eye damage/eye irritation	Category 2A
	Specific target organ toxicity, single exposure	Category 3 narcotic effects

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection/face protection.
Response	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Other hazards	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	69.75

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	12.65
Butane		106-97-8	12.35
Other components below	reportable levels		5.25

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Cupatial such a tive a surface and	Eirofightere must use standard protective equipment including flame retardant east, helmet with

Special protective equipment Firefighters must use standard protective equipment including flame retardant coat, helmet with and precautions for firefighters face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose equipment/instructions holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

> Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Specific methods

Fire fighting

Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch protective equipment and damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate emergency procedures closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without Methods and materials for containment and cleaning up risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. **Environmental precautions** Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Level 3 Aerosol.
	Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section

8. Exposure controls/personal protection

10 of the SDS).

US. ACGIH Threshold Limit Valu Components	Туре	Value
-		
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Canada. Alberta OELs (Occupati		
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	1800 mg/m3
		750 ppm
	TWA	1200 mg/m3
		500 ppm
Butane (CAS 106-97-8)	TWA	1000 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
Canada. British Columbia OELs. Safety Regulation 296/97, as am		s for Chemical Substances, Occupational Health and
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	750 ppm
	TWA	600 ppm
Canada. Manitoba OELs (Reg. 2′	17/2006. The Workplace Safety	And Health Act)
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Canada. Ontario OELs. (Control	of Exposure to Biological or C	hemical Agents)
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	TWA	500 ppm
Butane (CAS 106-97-8)	TWA	800 ppm
Canada. Quebec OELs. (Ministry	of Labor - Regulation Respect	ting the Quality of the Work Environment)
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	2380 mg/m3
		1000 ppm
	TWA	1190 mg/m3
		500 ppm
Butane (CAS 106-97-8)	TWA	1900 mg/m3
	TWA	800 ppm

Product name: Fresh Linen Metered Air Freshener

Components		Туре	Va	lue	
			10	00 ppm	
ological limit values					
ACGIH Biological Expos					
Components	Value	Determinant	Specimen	Sampling Time	
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*	
* - For sampling details, pl	ease see the source	e document.			
ntrols dividual protection measur	or other engine exposure limite eyewash statio	eering controls to mainta s have not been establis on.	ain airborne leve shed, maintain ai	cess enclosures, local exha ls below recommended expo rborne levels to an acceptab	osure limits. If
Eye/face protection	Wear safety g	lasses with side shields	(or goggles).		
Skin protection					
Hand protection	Wear appropri supplier.	ate chemical resistant g	loves. Suitable g	loves can be recommended	by the glove
Other	Wear suitable	protective clothing.			
Respiratory protection	If permissible air-supplied re		e NIOSH mechar	nical filter / organic vapor car	tridge or an
Thermal hazards	Wear appropri	ate thermal protective c	lothing, when ne	cessary.	
eneral hygiene Insiderations	after handling		eating, drinking,	onal hygiene measures, suc and/or smoking. Routinely	

9. Physical and chemical properties

Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	132.89 °F (56.05 °C) estimated
Flash point	-156.0 °F (-104.4 °C) PROPELLANT estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	2.4 % estimated
Flammability limit - upper (%)	12 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	60 - 70 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.784 estimated
10. Stability and reactivit	/

To: Otability and Todottity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity	Narcotic effects.	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Dermal		
LD50	Guinea pig	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Butane (CAS 106-97-8)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes

Components	Species		Test Results
	Rat		1355 mg/l
Propane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation			
LC50	Mouse		1237 mg/l, 120 Minutes
			52 %, 120 Minutes
	Rat		1355 mg/l
			658 mg/l/4h
* Estimates for product may	be based on add	ditional component data not shown.	
Skin corrosion/irritation	Prolonged sk	in contact may cause temporary irritation	on.
Serious eye damage/eye rritation	Causes serio	us eye irritation.	
Respiratory or skin sensitizatio	on		
Respiratory sensitization	Not a respira	tory sensitizer.	
Skin sensitization	This product	is not expected to cause skin sensitiza	tion.
Germ cell mutagenicity	No data avai mutagenic or	able to indicate product or any compor genotoxic.	ents present at greater than 0.1% are
Carcinogenicity			
ACGIH Carcinogens			
Acetone (CAS 67-64-1) Canada - Manitoba OELs: d	carcinogenicity		is a human carcinogen.
ACETONE (CAS 67-64-	1)	Not classifiable as a	human carcinogen.
Reproductive toxicity	This product	is not expected to cause reproductive of	or developmental effects.
Specific target organ toxicity - single exposure	May cause d	rowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified	l.	
Aspiration hazard	Not likely, du	e to the form of the product.	
12. Ecological informatio	n		
Ecotoxicity		The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment	
Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic	5050		
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
* Estimates for product may	be based on add	ditional component data not shown.	
Persistence and degradability	No data is av	ailable on the degradability of this proc	luct.
Bioaccumulative potential			
Partition coefficient n-	octanol / water		
Acetone		-0.24	
Butane Propane		2.89 2.36	
Nobility in soil	No data avai		
Other adverse effects			depletion, photochemical ozone creation
			ntial) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

т	
	DG

100	
UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	D
Special precautions for user	Not available.
	tion requirements and may be shipped as a limited quantity.
IATA	
UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo	Allowed with restrictions.
aircraft	
Cargo aircraft only	Allowed with restrictions.
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	F-D, S-U
· ·	Read safety instructions, SDS and emergency procedures before handling.
Transport in bulk according to	Not applicable.
Annex II of MARPOL 73/78 and	
the IBC Code	

IATA; IMDG; TDG



15. Regulatory information

Canadian regulations		
Controlled Drugs and Subst	ances Act	
Not regulated.		
Export Control List (CEPA 1	999, Schedule 3)	
Not listed.		
Greenhouse Gases		
Not listed.		
Precursor Control Regulatio	ns	
Acetone (CAS 67-64-1)	Class B	
International regulations		
Stockholm Convention		
Not applicable. Rotterdam Convention		
Not applicable.		
Kyoto protocol		
Not applicable.		
Montreal Protocol		
Not applicable. Basel Convention		
Not applicable.		
International Inventories		
		.
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes
	and a file and the second control of the data for an example of the second second second by the second by the s	

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date	01-05-2016
Revision date	05-19-2017
Version #	02

	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names