SAFETY DATA SHEET

1. Identification

Product identifier RA009C_Disinfectant Surface Cleaner

Other means of identification

Product code 1000008418 Recommended use DISINFECTANT Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Pro-Link Canada Company name

Box 67082, 421 Richmond Road **Address**

Ottawa, Ontario K2A 4E4

Canada

Telephone General Assistance 613-722-0798

Website www.prolinkcanada.com

Not available. E-mail

Emergency - US 1-866-836-8855 **Emergency phone number**

Emergency - Outside US 1-952-852-4646

Supplier Not available.

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 **Health hazards** Serious eye damage/eye irritation Category 2

Label elements



Signal word Danger

Extremely flammable aerosol. Causes serious eye irritation. **Hazard statement**

Precautionary statement

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Prevention

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Wash thoroughly after handling. Wear eye protection/face protection.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present Response

and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage

Disposal Dispose of waste and residues in accordance with local authority requirements.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|-----------------------|--------------------------|------------|-----------|
| 2-butoxyethanol | | 111-76-2 | 3 - 7 |
| Butane | | 106-97-8 | 1 - 5 |
| EDTA Tetrasodium Salt | | 64-02-8 | 0.5 - 1.5 |
| Isopropyl Alcohol | | 67-63-0 | 0.5 - 1.5 |

Product name: RA009C Disinfectant Surface Cleaner

| Chemical name | Common name and synonyms | CAS number | % |
|------------------------|--------------------------|------------|-----------|
| Propane | | 74-98-6 | 0.5 - 1.5 |
| Other components below | reportable levels | | 60 - 100 |

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eve contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

Not available.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

equipment/instructions

Specific methods

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened

containers. In the event of fire and/or explosion do not breathe fumes.

Extremely flammable aerosol. General fire hazards

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

| US. ACGIH | Threshold | Limit | Values |
|-----------|-----------|-------|--------|
| | | | |

| US. ACGIH Threshold Limit Valu Components | es Type | Value |
|---|---------------------------------|--|
| 2-butoxyethanol (CAS 111-76-2) | TWA | 20 ppm |
| Butane (CAS 106-97-8) | STEL | 1000 ppm |
| sopropyl Alcohol (CAS 37-63-0) | STEL | 400 ppm |
| , | TWA | 200 ppm |
| Canada. Alberta OELs (Occupati | ional Health & Safety Code, Sci | hedule 1, Table 2) |
| Components | Туре | Value |
| 2-butoxyethanol (CAS 11-76-2) | TWA | 97 mg/m3 |
| | | 20 ppm |
| Butane (CAS 106-97-8) | TWA | 1000 ppm |
| sopropyl Alcohol (CAS 67-63-0) | STEL | 984 mg/m3 |
| 77 00 0) | | 400 ppm |
| | TWA | 492 mg/m3 |
| | | 200 ppm |
| Propane (CAS 74-98-6) | TWA | 1000 ppm |
| Safety Regulation 296/97, as am Components | | s for Chemical Substances, Occupational Health and Value |
| 2-butoxyethanol (CAS 111-76-2) | TWA | 20 ppm |
| Butane (CAS 106-97-8) | STEL | 750 ppm |
| | TWA | 600 ppm |
| sopropyl Alcohol (CAS 67-63-0) | STEL | 400 ppm |
| | TWA | 200 ppm |
| Canada. Manitoba OELs (Reg. 2 ⁻ | 17/2006, The Workplace Safety | And Health Act) |
| Components | Туре | Value |
| 2-butoxyethanol (CAS 11-76-2) | TWA | 20 ppm |
| Butane (CAS 106-97-8) | STEL | 1000 ppm |
| sopropyl Alcohol (CAS 67-63-0) | STEL | 400 ppm |
| | TWA | 200 ppm |
| Canada. Ontario OELs. (Control | | |
| Components | Туре | Value |
| 2-butoxyethanol (CAS 111-76-2) | TWA | 20 ppm |
| Butane (CAS 106-97-8) | TWA | 800 ppm |
| sopropyl Alcohol (CAS 67-63-0) | STEL | 400 ppm |
| | TWA | 200 ppm |
| | | |

SDS CANADA

| Canada. Quebec OELS. (Ministry Components | Type | ting the Quality of the Work Environment) Value |
|---|------|---|
| 2-butoxyethanol (CAS 111-76-2) | TWA | 97 mg/m3 |
| , | | 20 ppm |
| Butane (CAS 106-97-8) | TWA | 1900 mg/m3 |
| | | 800 ppm |
| Isopropyl Alcohol (CAS 67-63-0) | STEL | 1230 mg/m3 |
| , | | 500 ppm |
| | TWA | 983 mg/m3 |
| | | 400 ppm |
| Propane (CAS 74-98-6) | TWA | 1800 mg/m3 |
| | | 1000 ppm |

Biological limit values

| Components | Value | Determinant | Specimen | Sampling Time |
|-----------------------------------|----------|--|---------------------|---------------|
| 2-butoxyethanol (CAS 111-76-2) | 200 mg/g | Butoxyacetic acid (BAA), with hydrolysis | Creatinine in urine | * |
| Isopropyl Alcohol (CAS 67-63-0) | 40 mg/l | Acetone | Urine | * |

^{* -} For sampling details, please see the source document.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an Respiratory protection

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Gas. **Form** Aerosol. Color Not available. Not available. Odor Odor threshold Not available. Not available. Melting point/freezing point Not available.

Initial boiling point and boiling

range

212 °F (100 °C) estimated

-156.0 °F (-104.4 °C) PROPELLANT estimated Flash point

Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%) Vapor pressure

Not available. Not available.

Vapor density Relative density Not available.

Not available.

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature

473 °F (245 °C) estimated

Decomposition temperature Viscosity

Not available. Not available.

Other information

Explosive properties

Not explosive. Not oxidizing.

Specific gravity

Oxidizing properties

0.922 estimated

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

reactions

Possibility of hazardous

Hazardous polymerization does not occur.

Conditions to avoid

Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials

Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

No adverse effects due to inhalation are expected. Inhalation

Skin contact

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Eve contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and

toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Information on toxicological effects

Acute toxicity

| Components | Species | Test Results | |
|--------------------------|------------|----------------------|--|
| 2-butoxyethanol (CAS 111 | -76-2) | | |
| <u>Acute</u> | | | |
| Dermal | | | |
| LD50 | Guinea pig | 7.3 ml/kg, 4 Days | |
| | | 0.23 ml/kg, 24 Hours | |
| | Rabbit | 435 mg/kg, 24 Hours | |
| | | 0.68 ml/kg, 24 Hours | |

| Components | Species | Test Results |
|-------------------------------|------------|------------------------|
| | | 0.63 ml/kg |
| | Rat | > 2000 mg/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rabbit | 400 ppm, 7 Hours |
| | Rat | 450 ppm, 4 Hours |
| Oral | | |
| LD100 | Rabbit | 695 mg/kg |
| LD50 | Dog | > 695 mg/kg |
| | Guinea pig | 1414 mg/kg |
| | Mouse | 1519 mg/kg |
| | Rat | 1746 mg/kg |
| Butane (CAS 106-97-8) | | |
| <u>Acute</u> | | |
| Inhalation | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes |
| | | 52 %, 120 Minutes |
| | Rat | 1355 mg/l |
| EDTA Tetrasodium Salt (CAS | 64-02-8) | |
| <u>Acute</u> | | |
| Oral | | |
| LD50 | Rat | 1658 mg/kg |
| Isopropyl Alcohol (CAS 67-63- | 0) | |
| Acute | | |
| Dermal | Dobbit | 16.4 ml/kg, 04 Hours |
| LD50 | Rabbit | 16.4 ml/kg, 24 Hours |
| Inhalation LC50 | Rat | > 10000 ppm, 6 Hours |
| Oral | Παι | > 10000 ppm, 6 mours |
| LD50 | Rat | 5.84 g/kg |
| Propane (CAS 74-98-6) | Tital | 5.5 T g/Ng |
| Acute | | |
| Inhalation | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes |
| | | 52 %, 120 Minutes |
| | Rat | 1355 mg/l |
| | | 658 mg/l/4h |
| | | 555 g |

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

2-butoxyethanol (CAS 111-76-2) Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

2-butoxyethanol (CAS 111-76-2) A3 Confirmed animal carcinogen with unknown relevance to

humans.

Isopropyl Alcohol (CAS 67-63-0) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

2-BUTOXYETHANOL (EGBE) (CAS 111-76-2)

Confirmed animal carcinogen with unknown relevance to humans.

This product is not expected to cause reproductive or developmental effects.

2-PROPANOL (CAS 67-63-0) Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

2-butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

Not classified.

repeated exposure

Aspiration hazard Not likely, due to the form of the product. **Chronic effects** May be harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Components | | Species | Test Results |
|-----------------------|-------------------|---------------------------------------|--------------------------|
| 2-butoxyethanol (CAS | 3 111-76-2) | | |
| Aquatic | | | |
| Fish | LC50 | Inland silverside (Menidia beryllina) | 1250 mg/l, 96 hours |
| EDTA Tetrasodium Sa | alt (CAS 64-02-8) | | |
| Aquatic | | | |
| Algae | IC50 | Algae | 1.01 mg/L, 72 Hours |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | 472 - 500 mg/l, 96 hours |
| Isopropyl Alcohol (CA | S 67-63-0) | | |
| Aquatic | | | |
| Algae | IC50 | Algae | 1000.0001 mg/L, 72 Hours |
| Crustacea | EC50 | Daphnia | 13299 mg/L, 48 Hours |
| Fish | LC50 | Bluegill (Lepomis macrochirus) | > 1400 mg/l, 96 hours |
| | | | |

^{*} Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

2-butoxyethanol 0.83 2.89 Butane Isopropyl Alcohol 0.05 Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents **Disposal instructions**

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

TDG

UN number UN1950

UN proper shipping name AEROSOLS, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -

Packing group Not applicable.

Environmental hazards D

Special precautions for user Not available.

This product meets the exemption requirements and may be shipped as a limited quantity.

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950 UN proper shipping name AEROSOLS

Transport hazard class(es)

Class 2.1 Subsidiary risk -Label(s) 2.1

Packing group Not applicable.

Environmental hazards

Marine pollutant No. EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code



15. Regulatory information

Canadian regulations

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region

| | | - · · · · · · · · · · · · · · · · · · · |
|-------------|--|---|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | Yes |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other Information

Issue date 11-26-2018

Version # 01

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision information Product and Company Identification: Alternate Trade Names

Inventory name

Product #: 1000008418 | Version #: 01 | Issue date: 11-26-2018

On inventory (yes/no)*

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).