

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number YA006C
Product name Pro-Link Furniture Polish
Effective date 10-Aug-2012
Company information Pro-Link, Inc.
Ottawa, ON K1Z 1E9 Canada
Company phone General Assistance 1-800-74-LINKS
Emergency telephone US 1-866-836-8855
Emergency telephone outside US 1-952-852-4646
Version # 12
Supersedes date 09-Jun-2011
Expiry Date 10-Aug-2015
Product use Furniture polish

2. Hazards Identification

Emergency overview Aerosol. Heat may cause the containers to explode. CONTENTS UNDER PRESSURE.
Potential health effects
Eyes Health injuries are not known or expected under normal use.
Skin Health injuries are not known or expected under normal use.
Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Health injuries are not known or expected under normal use.
Ingestion Exposure by ingestion of an aerosol is unlikely.
Target organs Central nervous system.

3. Composition / Information on Ingredients

Components	CAS #	Percent
n-Butane	106-97-8	1 - 5
Propane	74-98-6	0.5 - 1.5
Non-hazardous and other components below reportable levels		60 - 100

4. First Aid Measures

First aid procedures
Eye contact Flush eyes with water as a precaution. Get medical attention if irritation develops and persists.
Skin contact Rinse with water. Get medical attention if irritation develops and persists.
Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Ingestion In the unlikely event of swallowing contact a physician or poison control center. No need for first aid is anticipated if material is swallowed.

5. Fire Fighting Measures

Flammable properties Heat may cause the containers to explode. Ruptured cylinders may rocket.
Extinguishing media
Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Protection of firefighters
Protective equipment and precautions for firefighters Containers should be cooled with water to prevent vapor pressure build up. Some of these materials, if spilled, may evaporate leaving a flammable residue. Do not direct water at source of leak or safety devices as icing may occur. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Unusual fire & explosion hazards Heat may cause the containers to explode. Ruptured cylinders may rocket.

6. Accidental Release Measures

Methods for containment Stop leak if you can do so without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). If possible, turn leaking containers so that gas escapes rather than liquid. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewer, basements or confined areas.

Methods for cleaning up Clean up in accordance with all applicable regulations. Should not be released into the environment. Ventilate the area. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

7. Handling and Storage

Handling Pressurized container: Do not pierce or burn, even after use. When using do not smoke. DO NOT handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not use if spray button is missing or defective. Do not re-use empty containers.

Storage Contents under pressure. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Avoid exposure to long periods of sunlight. Keep at temperature not exceeding 49 °C. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Level 1 Aerosol (NFPA 30B)

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components

CAS

TWA

STEL

Ceiling

n-Butane	106-97-8	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

Personal protective equipment

Eye / face protection

Not normally needed.

Respiratory protection

No personal respiratory protective equipment normally required. If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance Film.

Boiling point 188.6 °F (87.2 °C) estimated

Color White.

Evaporation rate Not available

Flammability (HOC) 4.2926 kJ/g estimated

Flammability limits in air, lower, % by volume Not available

Flammability limits in air, upper, % by volume Not available

Flash back No

Flash point -156 °F (-104.4 °C) estimated

Form Compressed gas. Aerosol.

Freezing point Not available

Odor fruity

Odor threshold Not available

pH 10 - 11

Physical state Liquid.

Pressure 65 - 85 psig @ 70F
Specific gravity 0.9668 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition.
Conditions to avoid Aerosol containers are unstable at temperatures above 49°C.
Incompatible materials None known.

11. Toxicological Information

Acute effects Acute LC50: 3311 mg/l/4h estimated, Rat, Inhalation
Acute LD50: 26282 mg/kg estimated, Rat, Dermal

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

n-Butane	106-97-8	Inhalation LC50 Rat 658 mg/L 4 h
Propane	74-98-6	Inhalation LC50 Rat 658 mg/L 4 h

Sensitization Not expected to be hazardous by WHMIS criteria.
Carcinogenicity Not expected to be hazardous by WHMIS criteria.
Mutagenicity Not expected to be hazardous by WHMIS criteria.
Teratogenicity Not expected to be hazardous by WHMIS criteria.
Chronic toxicity Not expected to be hazardous by WHMIS criteria.

12. Ecological Information

Ecotoxicity LC50 3429 mg/L, Fish, 96.00 Hours,
EC50 26718 mg/L, Daphnia, 48.00 Hours,
Contains a substance which causes risk of hazardous effects to the environment.

13. Disposal Considerations

Disposal instructions Contents under pressure. Dispose of this material and its container to hazardous or special waste collection point. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001.

14. Transport Information

Canadian Transportation of Dangerous Goods (TDG) Requirements

Proper shipping name	AEROSOLS, flammable
Hazard class	2.1
UN number	UN1950
Marine pollutant	•
Special provisions	80 SOR/2002-306
Packaging exceptions	If <1L: Consumer Commodity




15. Regulatory Information

Canadian regulations This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Canada - WHMIS - Ingredient Disclosure List

n-Butane	106-97-8	1 %
----------	----------	-----

WHMIS status Controlled
WHMIS classification A - Compressed Gas
WHMIS labeling



Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information in the sheet was written based on the best knowledge and experience currently available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

MSDS sections updated

This document has undergone significant changes and should be reviewed in its entirety.

Prepared by

Regulatory Compliance